



**Material Safety Data Sheet**  
 Golden West Dexron VI  
 Automatic Transmission Fluid

<b>Material Safety Data Sheet</b> May be used to comply with OSHA's Hazard Communication Standard, 39 CFR 1910.1200. Standard must be 39 CFR 1910.1200. Standard must be consulted for specific requirements.		U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072		
Identity (As Used on Label and List) Golden West DIII/M ATF		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.		
<b>Section I</b>				
Manufacturer's Name Golden West Packaging Plant		Emergency Telephone Number 210-649-1401		
Address (Number, street, city, state and ZIP code) 13598 Hwy 87 East Adkins, TX 78101		Telephone Number for Information 210-649-1401		
		Date Prepared 2007		
		Signature of Preparer (optional)		
<b>Section II - Hazardous Ingredients/Identity Information</b>				
Methacrylate Copolymer  Low order of toxicity. Excessive exposure may result in eye, skin, or respiratory irritation. High pressure injection under skin may cause serious damage.  Health - 0 Flammability -1 Reactivity -0		CAS# Confidential	Concentration 1-5%	
<b>Section III - Physical/Chemical Characteristics</b>				
Boiling Point	>316°C	Specific Gravity (H2O = 1)		
Vapor Pressure (mm Hg.)	<0.013kPa	Melting Point	N.A.	
Vapor Density (AIR = 1)	>2@101kPa	Evaporation Rate (Butyl Acetate = 1)	N.D.	
Solubility in Water - Negligible				
Appearance and Odor - Red				
<b>Section IV - Fire and Explosion Hazard Data</b>				
Flash Point (Method Used)	180°C	Flammable Limits	LEL	UEL
		N.D.	0.9	7.0
Extinguishing Media - Use water fog, foam, dry chemical or carbon dioxide (C)2 to extinguish flames.				
Special Fire Fighting Procedures - Use water to cool fire exposed containers. Use water to disperse spilled liquid.				
Unusual Fire Explosion Hazards - None				
Style CU-FP 174 Labelmaster, Div. Of American Labelmark Co. Inc. 60646			OSHA 174, Sept. 1985	

<b>Section V - Reactivity Data</b>				
Stability - Stable under normal conditions		Conditions to Avoid - High heat. Exposure to flame.		
Incompatibility (Materials to Avoid) - Strong oxidizers				
Hazardous Decomposition or Byproducts - Material does not decompose at ambient temperatures				
Hazardous Polymerization	May Occur	Conditions to Avoid - High heat. Exposure to flame.		
	Will Not Occur - X			
<b>Section VI - Health Hazard Data</b>				
Route(s) of Entry:		Inhalation? Vapor when heated	Skin? No prolong use	Ingestion? Possible
Health Hazards (Acute and Chronic) - Minimally irritating to eyes. Can cause redness if exposed to skin for prolonged periods.				
Carcinogenicity: N.A.	NTP?	IARC Monographs?	OSHA Regulated?	
Signs and Symptoms of Exposure - See above.				
Medical Conditions Generally Aggravated - Edema or redness to skin.				
Emergency First Aid Procedures - Wash off with soap & water.				
<b>Section VII - Precautions for Safe Handling and Use</b>				
Steps to be Taken in Case Material is Released or Spilled - Minimum reasonable handling procedures are required. Avoid high temperatures.				
Waste Disposal Method - Clean up spill. Use absorbent material.				
Precautions to be Taken in Handling and Storing - Do not store in open or unlabelled containers.				
Other Precautions - None				
<b>Section VII - Control Measures</b>				
Respiratory Protection (Specify Type) - none				
Ventilation	Local Exhaust - O.K.	Special - N.A.		
	Mechanical (General) - N.A.	Other - N.A.		
Protective Gloves - N.A.				
Eye Protection - Safety glasses with side shields				
Work/Hygienic Practices - Chemical type goggles acceptable. Keep clean.				
U.S.G. P.O.: 1986-491-529/45775				