



Material Safety Data Sheet
Golden West Fleet Utrac

Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.	U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072
---	---

Identity (As Used on Label and List) Golden West Fleet Utrac	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
---	---

Section I

Manufacturer's Name Golden West Packaging Co.	Emergency Telephone Number 210-649-1401
Address (Number, street, city, state and ZIP code) 13598 Hwy 87 East Adkins, TX 78101	Telephone Number for Information 210-649-1401
	Date Prepared 2006
	Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Petroleum Hydrocarbon-Napthenic base stock -Additive package Health 1 Reactivity 0 Flammability 1	OSHA PEL No Limit	ACGIH TVL No Limit	Limits Recommended % (optional)
---	----------------------	-----------------------	------------------------------------

Section III - Physical/Chemical Characteristics

Boiling Point	650°F	Specific Gravity (H2O = 1)	20.2
Vapor Pressure (mm Hg.)	.09	Melting Point	N.A.
Vapor Density (AIR = 1)	Plus 1	Evaporation Rate (Butyl Acetate = 1)	.05

Solubility in Water - Negligible

Appearance and Odor - Dark amber color. Hydrocarbon odor.

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	350°F Open Dish	Flammable Limits	LEL	UEL
		No Data	N.A.	N.A.

Extinguishing Media - Use dry chemical, foam or Carbon Dioxide.

Special Fire Fighting Procedures - Water should be used to cool down containers.

Unusual Fire and Explosion Hazards - Dense smoke may be generated by burning product. Carbon Monoxide may result from combustion.

Section V - Reactivity Data				
Stability - Stable		Conditions to Avoid - High heat. Exposure to flame.		
Incompatibility (Materials to Avoid) -				
Hazardous Decomposition or Byproducts - Vapors may be minimally toxic.				
Hazardous Polymerization	May Occur	Conditions to Avoid - None; if exposure is within permissible concentrations.		
	Will Not Occur			
Section VI - Health Hazard Data				
Route(s) of Entry:		Inhalation? Vapor when heated.	Skin? No, unless prolonged use.	Ingestion? Possible
Health Hazards (Acute and Chronic) - Minimally irritating to eyes. Can cause redness if exposed to skin.				
Carcinogenicity: N.A.	NTP?	IARC Monographs?	OSHA Regulated?	
Signs and Symptoms of Exposure - See above.				
Medical Conditions Generally Aggravated by Exposure - Edema or redness to skin.				
Emergency First Aid Procedures - Wash off with soap and water.				
Section VII - Precautions for Safe Handling and Use				
Steps to be Taken in Case Material is Released or Spilled - Minimal reasonable handling procedures are required. Avoid high temperatures.				
Waste Disposal Method - Clean up spill. Use absorbent material.				
Precautions to be Taken in Handling and Storing- See above.				
Other Precautions - None				
Section VII - Control Measures				
Respiratory Protection (Specify Type) - None				
Ventilation	Local Exhaust - Yes	Special - N.A.		
	Mechanical (General) - None	Other - N.A.		
Protective Gloves - N.A.				
Eye Protection - See above.				
Other Protective Clothing or Equipment - N.A.				
Work/Hygienic Practices - Chemical type goggles acceptable. Keep hands clean.				
U.S.G. P.O.: 1986-491-529/45775				