



**Material Safety Data Sheet**  
Golden West Non Detergent 10 wt. Oil

<b>Material Safety Data Sheet</b> May be used to comply with OSHA's Hazard Communication Standard, 39 CFR 1910.1200. Standard must be 39 CFR 1910.1200. Standard must be consulted for specific requirements.		U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072		
Identity (As Used on Label and List) Golden West Non Detergent 10 wt. Oil		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.		
<b>Section I</b>				
Manufacturer's Name Golden West Packaging Plant		Emergency Telephone Number 210-649-1401		
Address (Number, street, city, state and ZIP code) 13598 Hwy 87 East Adkins, TX 78101		Telephone Number for Information 210-649-1401		
		Date Prepared 2005		
		Signature of Preparer (optional)		
<b>Section II - Hazardous Ingredients/Identity Information</b>				
Hazardous Components (Specific Chemical Identity; Common Name(s) Petroleum Hydrocarbon Mineral Oil	Health 1 Flammability 1 Reactivity 0	OSHA PEL	ACGIH TVL No Limit	Limits Recommended % (optional)
<b>Section III - Physical/Chemical Characteristics</b>				
Boiling Point	515°F	Specific Gravity (H2O = 1)	.0921	
Vapor Pressure (mm Hg.)	-1	Melting Point	N.A.	
Vapor Density (AIR = 1)	1+	Evaporation Rate (Butyl Acetate = 1)	-1	
Solubility in Water - Negligible				
Appearance and Odor - Light to Dark Amber Color				
<b>Section IV - Fire and Explosion Hazard Data</b>				
Flash Point (Method Used)	315°F ASTMD-92	Flammable Limits N.D.	LEL N.A.	UEL N.A.
Extinguishing Media - CO2, Water Spray or fog, foam, dry chemical				
Special Fire Fighting Procedures - Cool exposed containers with water spray.				
Unusual Fire Explosion Hazards - Pressure increase in heated containers.				
Style CU-FP 174 Labelmaster, Div. Of American Labelmark Co. Inc. 60646			OSHA 174, Sept. 1985	

<b>Section V - Reactivity Data</b>			
Stability - Unstable		Conditions to Avoid - Extreme Heat	
Incompatibility (Materials to Avoid) - Strong oxidants			
Hazardous Decomposition or Byproducts - Partial, burning produces, fumes, smoke and Carbon Monoxide			
Hazardous Polymerization	May Occur	Conditions to Avoid -	
	Will Not Occur - X		
<b>Section VI - Health Hazard Data</b>			
Route(s) of Entry:	Inhalation? Yes	Skin? Yes	Ingestion? Possible
Health Hazards (Acute and Chronic) - Prolonged exposure with skin will dry and defat the skin, leading to irritation and dermatitis. Inhalation with fumes in high concentration.			
Carcinogenicity:	NTP? N.A.	IARC Monographs? N.A.	OSHA Regulated?
Signs and Symptoms of Exposure - Dizziness, headache and respiratory irritation.			
Medical Conditions Generally Aggravated - ARC states that there is sufficient evidence that oil of this type can cause cancer in laboratory animals after frequent exposure over their lifetime.			
Emergency First Aid Procedures - If overcome by fumes, remove from exposure, call a doctor. If breathing is irregular or stopped. Start resuscitation, administer oxygen. If ingested induce vomiting. Call a doctor. Wash from skin.			
<b>Section VII - Precautions for Safe Handling and Use</b>			
Steps to be Taken in Case Material is Released or Spilled - Keep containers closed when not in use. Do not store near flames.			
Waste Disposal Method - According to local, state and federal law.			
Precautions to be Taken in Handling and Storing - Avoid breathing fumes. Wash skin thoroughly with soap/warm water after handling.			
Other Precautions - Use chemical resistant gloves.			
<b>Section VII - Control Measures</b>			
Respiratory Protection (Specify Type) - Avoid fumes.			
Ventilation	Local Exhaust - O.K.	Special - N.A.	
	Mechanical (General) -	Other -	
Protective Gloves - Yes			
Eye Protection - Goggles			
Other Protective Clothing or Equipment - Avoid contact with skin.			
Work/Hygienic Practices - Wash exposed body parts with soap and water after exposure.			
U.S.G. P.O.: 1986-491-529/45775			