



Material Safety Data Sheet
Golden West Rock Drill Oil 150

Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.		U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072		
Identity (As Used on Label and List) Golden West Rock Drill Oil 150		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.		
Section I				
Manufacturer's Name Golden West Packaging Co.		Emergency Telephone Number 210-649-1401		
Address (Number, street, city, state and ZIP code) 13598 Hwy 87 East Adkins, TX 78101		Telephone Number for Information 210-649-1401		
		Date Prepared 2006		
		Signature of Preparer (optional)		
Section II - Hazardous Ingredients/Identity Information				
Solvent - Dewaxed Paraffinic Petroleum. To the best of our knowledge, none of the above listed components is hazardous according to OSHA (1910.1200). Health 1 Reactivity 0 Flammability 1		OSHA PEL	ACGIH TVL	Limits Recommended % (optional)
Section III - Physical/Chemical Characteristics				
Boiling Point	600°F	Specific Gravity (H2O = 1)	150	
Vapor Pressure (mm Hg.)	< 1	Melting Point	N.A.	
Vapor Density (AIR = 1)	1+	Evaporation Rate (Butyl Acetate = 1)	<1	
Solubility in Water - negligible				
Light 2 color non staining - Light to dark amber color. Hydrocarbon odor.				
Section IV - Fire and Explosion Hazard Data				
Flash Point (Method Used)	400°F	Flammable Limits	LEL	UEL
		N.D.	N.D.	N.D.
Extinguishing Media - Use dry chemical, foam or carbon dioxide.				
Special Fire Fighting Procedures - Use water to cool fire exposed containers. Use water to disperse spilled liquid.				
Unusual Fire and Explosion Hazards - None				
Style CU-FP 174 Labelmaster, Div. Of American Labelmark Co. Inc. 60646			OSHA 174, Sept. 1985	

Section V - Reactivity Data				
Stability - Stable		Condition to Avoid - High heat. Exposure to flame.		
Incompatibility (Materials to Avoid) -				
Hazardous Decomposition or Byproducts - Vapors may be minimally toxic.				
Hazardous Polymerization	May Occur	Conditions to Avoid - None; if exposure within permissible concentrations.		
	Will Not Occur			
Section VI - Health Hazard Data				
Route(s) of Entry:		Inhalation? Vapor when heated	Skin? No prolonged use	Ingestion? Possible
Health Hazards (Acute and Chronic) - Minimally irritating to eyes. Can cause redness if exposed to skin for prolonged periods.				
Carcinogenicity: N.A.	NTP?	IARC Monographs?	OSHA Regulated?	
Signs and Symptoms of Exposure - See above.				
Medical Conditions Generally Aggravated - Edema or redness to skin.				
Emergency First Aid Procedures - Wash off with soap and water.				
Section VII - Precautions for Safe Handling and Use				
Steps to be Taken in Case Material is Released or Spilled - Minimum reasonable handling procedures are required. Avoid high temperatures.				
Waste Disposal Method - Clean up spill. Use absorbent material.				
Precautions to be Taken in Handling and Storing- See above.				
Other Precautions - None				
Section VII - Control Measures				
Respiratory Protection (Specify Type) -None				
Ventilation -	Local Exhaust - O.K.	Special - N.A.		
	Mechanical (General) - None	Other - N.A.		
Protective Gloves - N.A.				
Other Protective Clothing or Equipment - N.A.				
Eye Protection - See above.				
Work/Hygienic Practices - Chemical type goggles acceptable. Keep clean.				
U.S.G. P.O.: 1986-491-529/45775				