



**Material Safety Data Sheet**  
Golden West Series 3 - 30WT

<b>Material Safety Data Sheet</b> May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.		U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072		
Identity (As Used on Label and List) Golden West Series 3 - 30WT		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.		
<b>Section I</b>				
Manufacturer's Name Golden West Packaging Co.		Emergency Telephone Number 210-649-1401		
Address (Number, street, city, state and ZIP code) 13598 Hwy 87 East Adkins, TX 78101		Telephone Number for Information 210-649-1401		
		Date Prepared 2006		
		Signature of Preparer (optional)		
<b>Section II - Hazardous Ingredients/Identity Information</b>				
Solvent - Dewaxed Paraffinic Petroleum with additive Package. To the best of knowledge, none of the above listed components are hazardous according to OSHA (1910.1200). Health 1 Reactivity 0 Flammability 1		OSHA PEL	ACGIH TVL	Limits Recommended % (optional)
<b>Section III - Physical/Chemical Characteristics</b>				
Boiling Point	850 °F	Specific Gravity (H2O = 1)	27.6	
Vapor Pressure (mm Hg.)	<1	Melting Point	N.A.	
Vapor Density (AIR = 1)	1+	Evaporation Rate (Butyl Acetate = 1)	<1	
Solubility in Water - Negligible				
Appearance and Odor - Light to dark amber. Hydrocarbon odor.				
<b>Section IV - Fire and Explosion Hazard Data</b>				
Flash Point (Method Used)	466 °F	Flammable Limits N.D.	LEL N.D.	UEL N.D.
Extinguishing Media - Water spray, dry chemical, foam or Carbon Dioxide.				
Special Fire Fighting Procedures - Use water to cool fire exposed containers. Use water to disperse spilled liquid.				
Unusual Fire and Explosion Hazards - None				
Style CU-FP 174 Labelmaster, Div. Of American Labelmark Co. Inc. 60646			OSHA 174, Sept. 1985	

<b>Section V - Reactivity Data</b>				
Stability - Stable		Conditions to Avoid - High heat. Exposure to flame.		
Incompatibility (Materials to Avoid) -				
Hazardous Decomposition or Byproducts - Vapors may be minimally toxic.				
Hazardous Polymerization	May Occur	Conditions to Avoid - None: If Exposure within permissible concentration.		
	Will Not Occur			
<b>Section VI - Health Hazard Data</b>				
Route(s) of Entry:		Inhalation? Vapor when heated	Skin? No Prolonged use	Ingestion? Possible
Health Hazards (Acute and Chronic) - Minimally irritating to eyes. Can cause redness if exposed to skin for prolonged periods.				
Carcinogenicity: N.A.	NTP?	IARC Monographs?	OSHA Regulated?	
Signs and Symptoms of Exposure - See above.				
Medical Conditions Generally Aggravated - Edema or redness to skin.				
Emergency First Aid Procedures - Wash off with soap and water.				
<b>Section VII - Precautions for Safe Handling and Use</b>				
Steps to be Taken in Case Material is Released or Spilled - Minimum reasonable handling procedures are required. Avoid high temperatures.				
Waste Disposal Method - Clean up spill. Use absorbent material.				
Precautions to be Taken in Handling and Storing - See above.				
Other Precautions - None				
<b>Section VII - Control Measures</b>				
Respiratory Protection (Specify Type) - Required when product burned. Use breathing equipment.				
Ventilation	Local Exhaust - O.K.	Special - N.A.		
	Mechanical (General) - None	Other - N.A.		
Protective Gloves - N.A.				
Eye Protection - See above.				
Other Protective Clothing or Equipment - N.A.				
Work/Hygienic Practices - Chemical type goggles acceptable. Keep clean.				
U.S.G. P.O.: 1986-491-529/45775				