



Material Safety Data Sheet
Golden West Synthetic Trans-Fluid 50

Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.		U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072	
Identity (As Used on Label and List) Golden West Synthetic Trans-Fluid 50		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.	
Section I			
Manufacturer's Name Golden West Packaging Co.		Emergency Telephone Number 210-649-1401	
Address (Number, street, city, state and ZIP code) 13598 Hwy 87 East Adkins, TX 78101		Telephone Number for Information 210-649-1401	
		Date Prepared 2007	
		Signature of Preparer (optional)	
Section II - Hazardous Ingredients/Identity Information			
Synthetic Base Oil with Additive Package	Health	2	
	Flammability	1	
	Reactivity	0	
Section III - Physical/Chemical Characteristics			
Boiling Point - 600°F		Specific Gravity (H2O = 1)	0.83
Vapor Pressure -		Melting Point	N.A.
Vapor Density (AIR = 1) -		Evaporation Rate (Butyl Acetate = 1)	
Solubility in Water - None			
Appearance and Odor - Amber			
Section IV - Fire and Explosion Hazard Data			
Flash Point (Method Used)	435°F	Flammable Limits - Flammable	LEL - N.E. UEL - N.E.
Extinguishing Media - Foam or dry chemical.			
Special Fire Fighting Procedures - CO2 and foam			
Unusual Fire and Explosion Hazards - Can emit toxic fumes when burned.			
Style CU-FP 174 Labelmaster, Div. Of American Labelmark Co. Inc. 60646		OSHA 174, Sept. 1985	

Section V - Reactivity Data			
Stability - Stable		Conditions to Avoid - N.A.	
Incompatibility (Materials to Avoid) -			
Hazardous Decomposition or Byproducts - Fumes can be toxic when burned.			
Hazardous Polymerization - N.A.	May Occur	Conditions to Avoid - Avoid storing at high temps over 500°F	
	Will Not Occur - X		
Section VI - Health Hazard Data			
Route(s) of Entry:		Inhalation? Yes	Skin? Yes
Ingestion? Yes			
Health Hazards (Acute and Chronic) - Avoid vapors when burned.			
Carcinogenicity: Mild	NTP?	IARC Monographs?	OSHA Regulated?
Signs and Symptoms of Exposure - Prolonged exposure to skin may cause irritation.			
Medical Conditions Generally Aggravated by Exposure - Rash can occur after prolonged exposure to skin.			
Emergency First Aid Procedures - Wash thoroughly with soap and water after exposure.			
Section VII - Precautions for Safe Handling and Use			
Steps to be Taken in Case Material is Released or Spilled - Clean up with oil. Dry and avoid contact with skin.			
Waste Disposal Method - Dispose according to state and federal rules.			
Precautions to be Taken in Handling and Storing - Store in dry, well ventilated area.			
Other Precautions - None			
Section VIII - Control Measures			
Respiratory Protection (Specify Type) - Required			
Ventilation - N.A.	Local Exhaust - ok	Special -	
	Mechanical (General) -	Other -	
Protective Gloves - Recommended			
Eye Protection - Always use eye protection when handling oil products.			
Other Protective Clothing or Equipment - Eye wash station.			
Work/Hygienic Practices - Wash exposed areas with soap and water.			
U.S.G. P.O.: 1986-491-529/45775			