



Material Safety Data Sheet
Golden West Twin Disc Fluid

Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.		U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072		
Identity (As Used on Label and List) Golden West Twin Disc Fluid		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.		
Section I				
Manufacturer's Name Golden West Packaging Co.		Emergency Telephone Number 210-649-1401		
Address (Number, street, city, state and ZIP code) 13598 Hwy 87 East Adkins, TX 78101		Telephone Number for Information 210-649-1401		
		Date Prepared 2006		
		Signature of Preparer (optional)		
Section II - Hazardous Ingredients/Identity Information				
Combination of #2 Diesel Fuel, red dye, and Lubrizol 5178 J additive. Health 1 Reactivity 2 Flammability 0		OSHA PEL	ACGIH TVL	Limits Recommended % (optional)
Section III - Physical/Chemical Characteristics				
Boiling Point	313°F	Specific Gravity (H2O = 1)	1.078	
Vapor Pressure (mm Hg.)	<1	Melting Point	N.A.	
Vapor Density (AIR = 1)	<1	Evaporation Rate (Butyl Acetate = 1)	N.A.	
Solubility in Water - Negligible				
Appearance and Odor - Medium to Dark Red color. Diesel Fuel odor.				
Section IV - Fire and Explosion Hazard Data				
Flash Point (Method Used)	200°F	Flammable Limits No Data	LEL N.A.	UEL N.A.
Extinguishing Media - Use foam, chemical and/or water spray.				
Special Fire Fighting Procedures - Use water spray to cool down containers, then use foam or chemical to extinguish flame.				
Unusual Fire and Explosion Hazards - Dense smoke may be generated by burning product. Carbon Monoxide may result from burning product.				
Style CU-FP 174 Labelmaster, Div. Of American Labelmark Co. Inc. 60646			OSHA 174, Sept. 1985	

Section V - Reactivity Data			
Stability - Unstable		Conditions to Avoid - None	
Incompatibility (Materials to Avoid) - None			
Hazardous Decomposition or Byproducts - None			
Hazardous Polymerization -	May Occur	Conditions to Avoid -	
	Will Not Occur		
Section VI - Health Hazard Data			
Route(s) of Entry:	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) - Avoid breathing mist fumes. Avoid prolonged contact with skin. Do not store near food items.			
Carcinogenicity: N.A.	NTP?	IARC Monographs?	OSHA Regulated?
Signs and Symptoms of Exposure - Skin may become irritated with contact.			
Medical Conditions Generally Aggravated by Exposure - Skin irritation with prolonged contact.			
Emergency First Aid Procedures - Wash skin thoroughly with soap and water.			
Section VII - Precautions for Safe Handling and Use			
Steps to be Taken in Case Material is Released or Spilled - Remove ignition sources. Contain in safe area until clean up effected.			
Waste Disposal Method - Use general methods of Diesel Fuel cleanup.			
Precautions to be Taken in Handling and Storing - Avoid breathing fumes. Wash skin thoroughly after contact.			
Other Precautions -			
Section VII - Control Measures			
Respiratory Protection (Specify Type) - Required when product burned. Use breathing equipment.			
Ventilation	Local Exhaust - O.K.	Special -	
	Mechanical (General) -	Other -	
Protective Gloves - Recommended			
Eye Protection - Goggles			
Other Protective Clothing or Equipment - None required.			
Work/Hygienic Practices - Always wash exposed skin in soap-water solution.			
U.S.G. P.O.: 1986-491-529/45775			