



**Material Safety Data Sheet**  
Golden West Windshield Wash 0°

|   |                |   |                         |
|---|----------------|---|-------------------------|
| <b>Material Safety Data Sheet</b><br>May be used to comply with OSHA's Hazard Communication Standard, 39 CFR 1910.1200. Standard must be 39 CFR 1910.1200. Standard must be consulted for specific requirements.                                    |                | U.S. Department of Labor<br>Occupational Safety and Health Administration<br>(Non-Mandatory Form)<br>Form Approved<br>OMB No. 1218-0072         |                         |
| NFPA CODES: Health 1<br>Flammability - 2<br>Reactivity - 0  |                | Note - NFPA ratings are based on a 0-4 rating scale with 0 representing minimal hazards or risks and 4 representing extreme hazards or risks.   |                         |
| Identity (As Used on Label and List)<br>Golden West Windshield Wash 0°  |                | Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that. |                         |
| <b>Section I</b>  |                |   |                         |
| Manufacturer's Name<br>Golden West Packaging Plant  |                | Emergency Telephone Number<br>210-649-1401  |                         |
| Address (Number, street, city, state and ZIP code)<br>13598 Hwy 87 East<br>Adkins, TX 78101   |                | Telephone Number for Information<br>210-649-1401  |                         |
|   |                | Signature of Preparer (optional)<br>prepared 2005   |                         |
| <b>Section II - Composition/Information on Materials</b>  |                |   |                         |
| REPORTABLE COMPONENTS   | CAS Number     | mm HG @ Temp  | Percent                 |
| Methanol, Additives<br>Exposure Guidelines: Methanol<br>OSHA STD - 8HR TIME WEIGHTED AVG(TWA) 200PPM  | 67-56-1<br>N.A | 96.1 20C  | <28%<br><1%             |
| <b>Section III - Physical/Chemical Characteristics</b>  |                |   |                         |
| Boiling Point   | 180-200°F      | Specific Gravity (H2O = 1)  | 0.9770@70°F             |
| Vapor Pressure (mm Hg.)   |                | Melting Point   |                         |
| Vapor Density (AIR = 1)   | N.D.           | Evaporation Rate (Butyl Acetate = 1)  | N.D.                    |
| Solubility in Water - Completely Soluble  |                |   |                         |
| Appearance and Odor - Clear, blue liquid. Mild alcohol odor.  |                |   |                         |
| <b>Section IV - Fire and Explosion Hazard Data</b>  |                |   |                         |
| Flash Point (Method Used)   | 118°F (TCC)    | Explosive Limits for 100% Methanol  | LOWER: 6%<br>UPPER: 36% |
| Extinguishing Media - Dry chemical, carbon dioxide, water spray or foam. Water may be ineffective, but may be used to cool exposed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat.    |                |   |                         |
| Special Protective Equipment for Firefighters - Wear a self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. |                |   |                         |

Unusual Fire Explosion Hazards - Handle as flammable liquid. Methanol vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near container, even if it is empty.

Style CU-FP 174 Labelmaster, Div. Of American Labelmark Co. Inc. 60646

OSHA 174, Sept. 1985

### Section V - Reactivity Data

Stability - Stable

Conditions to Avoid - Excessive heat.

Incompatibility (Materials to Avoid) - Reactive metals such as aluminum and magnesium, strong acids, strong oxidizing agents.

Hazardous Decomposition or Byproducts - Carbon Dioxide and Carbon Monoxide.

Hazardous Polymerization -

May Occur

Conditions to Avoid -

Will Not Occur - X

### Section VI - Health Hazard Data

Route(s) of Entry:

Inhalation?  
vapor when heated

Skin?  
no prolonged use

Ingestion?  
Possible

Health Hazards (Acute and Chronic) -

INHALATION: Breathing of vapor or mist is possible. Breathing small amounts during normal handling is not likely to cause harmful effects. Breathing large amounts can be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits.

EYE: May cause mild irritation. Symptoms include stinging, tearing, and redness.

SKIN: May cause mild irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of the skin.

INGESTION: Swallowing this material may be harmful.

SYMPTOMS OF EXPOSURE: Symptoms of exposure may include: nausea, vomiting, diarrhea, irritation (nose, throat, airways), dizziness, drowsiness, weakness, fatigue, headache, unconsciousness, leg cramps, pain in the abdomen and lower back, blurred vision, shortness of breath, cyanosis (causes blue coloring of the skin and nails from lack of oxygen), visual impairment (including blindness).

Carcinogenicity:

No

NTP?

No

IARC Monographs?

No

OSHA Regulated?

No

Signs and Symptoms of Exposure - See above.

Medical Conditions Generally Aggravated by Exposure - Exposure to this material may aggravate any preexisting condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias.

Emergency First Aid Procedures -

INHALATION: Move individual to fresh air. If symptoms persist seek medical attention. If breathing is difficult administer oxygen provided a qualified operator is present.

EYE CONTACT: Flush immediately with large quantities of water for 15 minutes, lifting eye lids to ensure that all surfaces are flushed. Seek medical attention.

SKIN: Remove contaminated clothing and wash contaminated skin with large amounts of soap and water. If irritation persists, get medical attention. Launder clothing before reuse.

INGESTION: Seek medical attention immediately. If individual is conscious, they may dilute by drinking water. If individual is drowsy or unconscious, do not give anything by mouth. Under either circumstance, do not leave the individual unattended if at all possible. Contact a physician, medical facility, or poison control center immediately.

### Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled -Eliminate all ignition sources, such as flames, hot surfaces, and sources of electrical, static or frictional sparks. Absorb liquid with absorbent material. If necessary, contain spill by diking.

Waste Disposal Method - Dispose of in accordance with all applicable local, state and federal regulations.

Precautions to be Taken in Handling and Storing- No smoking or open flame in storage use or handling areas. Avoid storage with incompatible materials.

Other Precautions - Store in closed containers in a cool, dry, well ventilated area. Keep away from sparks and open flame.

**Section VII - Control Measures**

Respiratory Protection (Specify Type) - Use an NIOSH approved respirator when airborne concentrations exceed exposure limits.

Ventilation- Provide sufficient ventilation to maintain airborne concentrations below exposure limits.

Protective Gloves - Wear appropriate impermeable gloves.

Eye Protection - Use chemical safety glasses, goggles, or face shields for eye protection.

Other Protective Clothing or Equipment - It is the responsibility of the user to determine the proper protective equipment that is needed based on how the product will be used.

Work/Hygienic Practices - Wash thoroughly after handling.

**Section IX - Disclaimer**

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by LFK Industries, Inc., to be accurate. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or correctness.

The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and express disclaimer liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. It is the responsibility of the user to determine the safety, toxicity and suitability of his own use, handling and disposal of this product.