

Golden West Signature Lubricants are high-quality products that meet or exceed manufacturer's specifications at the most economical prices.



### PRODUCT SPECIFICATIONS



Available:



## **Benefits**

- Protects emission control systems
- · Outstanding oxidation stability
- Excellent low-temperature properties help speed cold starts
- Universal product for mixed fleet operations

#### **Allied Sales Company**

5005 E. 7th Street • Austin, TX 78702 Ph: (512) 385-2167 • Fax: (512) 385-0259

**Golden West San Antonio** 3010 Aniol Street • San Antonio, TX 78219 Ph: (800) 638-6628 • Fax: (210) 222-1034 United Oil & Grease Company Abilene 2702 Industrial Blvd. • Abilene, TX 79605 Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock 3100 Clovis Rd. • Lubbock, TX 79415 Ph: (806) 763-1818 • Fax: (806) 763-5447

#### Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380 Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo 5400 Santa Maria Ave. • Laredo, TX 78041 Ph: (800) 638-6628 • Fax: (210) 222-1034

#### **Golden West McAllen**

10721 North 10th St. • McAllen, TX 78504 Ph: (800) 638-6628 • Fax: (210) 222-1034

Mighty of DFW 7410 Sand Street • Fort Worth, TX 76118 Ph: (817) 590-9770



# Data Sheet: Premium SAE 15W-40 CK-4/SN Heavy-duty Diesel Engine Oil

GoldenWest Premium SAE 15W-40 CK-4/SN Heavy Duty Diesel Engine Oil – CK-4 is formulated for use in High-Speed four-stroke cycle diesel engines designed to meet 2017 model year on-highway and Tier 4 non-road exhaust emission standards as well as for previous model year diesel engines. This oil is formulated for use in all applications with diesel fuels ranging in sulfur content up to 500 ppm.

GoldenWest Premium SAE 15W-40 CK-4/SN Heavy Duty Diesel Engine Oil is designed to provide enhanced protection against oil oxidation, viscosity loss due to shear, and oil aeration as well as protection against catalyst poisoning, particulate filter blocking, engine wear, piston deposits, degradation of low- and high-temperature properties, and soot-related viscosity increase.

GoldenWest Premium SAE 15W-40 CK-4/SN Heavy Duty Diesel Engine Oil meets API Service Classification CK-4, CJ-4, Cl-4 PLUS, Cl-4, CH-4/SN. It is recommended for use in applications calling for Mack EOS-4.5, Volvo VDS-4.5, VDS-4, VDS-3, Caterpillar ECF-3, ECF-2, Cummins CES 20086 & CES 20081, Detroit Diesel DFS 93K222, DFS 93K218, Daimler MB 228.31, MAN M3575, MTU Category 2.1, Renault RLD-4, RLD-3, ACEA E9-2012, and E7. Approved for use in applications calling for Ford Specification WSS-M2C171-F1.

Typical Analysis:		
Product Data	Test Method	Typical Analysis
@40° C, cSt	D445	118.9
@100° C, cSt	D445	15.5
Viscosity Index	D2270	137
Pour Point °C (°F)	D97	-33 (-27)
Flash Point °C (°F)	D92	238 (460)
Sulfated Ash, wt. %	D874	1.0
Cold Crank Simulator, cP	D5293	6490/-20°C
Mini-Rotary Viscometer TP1, cP	D4684	25,100/-25°C
High Temp. High Shear, HTHS @150°C, cP	D4683	4.2
TBN	D2896	10