

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

S P E C I F I C A T I O N S

Data Sheet: EP Gear Oil 90W & 140W

0

Product Application:

DUCT

EP Gear Oils are recommended for many types of manual transmissions, differentials and final drives, including worm-type gear. Meets many requirements for EP Gear Oils, including API, GL-2, GL-3, GL-4, GL-5. This product is blended from quality gear socks. The additve type is Sulfur-Phosphorus. Can be used for extreme pressure, Hypoid, or multi-purpose type gear oils.





This product is formulated for limited slip differentials.

Typical Analysis:			
		SAE90	SAE140
Gravity	°API	22.4	22.8
Flash Point	COC, °F	425	580
Pour Point, °F	۴	-5	+15
Viscosity	cSt@40°C	212	955
	cSt@100°C	15.0	40.6
	cSt@40°C	1140	2675
	cSt@210°C	80	138
Viscosity Index		58	65

The values shown here are representative of current production. Some are controlled by manufacturing specifications while others are not. They may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702 Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio 3010 Aniol Street • San Antonio, TX 78219 Ph: (800) 638-6628 • Fax: (210) 222-1034 United Oil & Grease Company Abilene 2702 Industrial Blvd • Abilene, TX 79605 Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock 3100 Clovis Rd. • Lubbock, TX 79415 Ph: (806) 763-1818 • Fax: (806) 763-5447 **Golden West Corpus Christi** 710B Industrial Blvd. • Robstown, TX 78380 Ph: (800) 638-6628 • Fax: (210) 222-1034

5400 Santa Maria Ave. • Laredo, TX 78041

Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

80 10721 North 10th St. • McAllen, TX 78504

Golden West McAllen

Ph: (800) 638-6628 • Fax: (210) 222-1034



