



Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

Data Sheet: Premium Universal Tractor Fluid

Product Application:



Available:



Tractor Hydraulic is suitable for use where the following specifications are recommended:

John Deere: Quatrol, J20A, J20C, J21A, Hy-gard J14B/C, Type 303

International Harvester: Hy Tran, B-6

Massey Ferguson: M-1110, M-1127B, M-1129A, M01135 (European), M-1141 (Permatran III)

Allis Chalmers: Power Fluid 821 XL

White Farm Equipment: Q1705, Q1722, Q1766B (UHTF Type 55), Q1802, Q1826

J.I. Case/David Brown: TFD (JIC - 143/146),

Hi-Vis (JIC-185), JIC-144/145, MS-1204, MS-1205 (TFD II)/-1206 (powergard PTF)/-1207 (HyTran Plus) MS-1210 (TCH) and B-6

Ford New Holland: M2C86-A/B/C (European), M2C134-A/B/C/D, M2C41-B, M2C43, M2C53-A/B, M2C92-A

Detroit Diesel Allison Division: C-2, C-3, C-4 Fluid

Caterpillar: TO-2

Oliver: Type 55

Sauer-Sunstrand: HMS-103

Deutz: HTF

Versatile: HY-Gear (23M, 24M)

Stieger: HTF (SEMS 17001)

Vickers: I-2986-S

Kubota Universal Transdraulic Fluid: UTD

Golden West Tractor Hydraulic Fluid incorporates advanced additive with the finest base stocks to provide excellent performance in modern agri-industrial equipment. It provides superior extreme pressure protection for maximum gear life and capacity for wet brakes and P.T.O. clutches. Excellent wet noise suppression and filterability characteristics along with rust and corrosion inhibitors, water tolerance and wide temperature range performance.

Golden West Tractor Hydraulic Fluid is formulated with advanced detergent/dispersant, anti-wear, antioxidant, anti-rust and anti-foam additives. This additive package protects tractor transmissions, axles and hydraulic pumps. Special friction modifiers permit the wet brakes to hold properly and allow smooth engagement of power take-off clutches. Formulated to resist leakage and eliminate brake chatter in most applications.

Typical Analysis:

	Range
API Gravity @60°F	28-30
Viscosity Index	75-125
Pour Point, °F	-20 to -30
Flash Point, °F	300-400
Viscosity cSt@40°C	40-65
Viscosity cSt@100°C	7.5-9.5
Viscosity cSt@100°F	200-300

The values shown here are representative of current production. Some are controlled by manufacturing specifications while others are not. They may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS

